

Features	Brewmatic 02	Brewmatic 03 (Brewbloc only)	Brewmatic 05	Brewmatic 06
number of mash programmes	2	2	3	3, extendable to 20
number of wort programmes	1	1	1	1, extendable to 4
logic valve control system	Yes	Yes	No	No
processor controlled valve system	No	No	Yes	Yes
change of parameter during operation	only partly possible	only partly possible	Yes	Yes
LED-Display	Yes	Yes	No	No
LCD-Display	No	No	Yes	Yes
menu operated input	No	No	Yes via Display	Yes via Display
energy saving optimisation	No	No	No	Yes, auto-optimizing
manual emergency operation	Yes	Yes	Yes	Yes
mixed operation MAN/AUTO	Yes	Yes	Yes	Yes but supervised
limitation of use	only for 8 hl and 10 hl brewhouses	only Brewbloc	none	none
automatic overboiling prevention	only via heating	only via heating	heating heating, agitator, pressure relief	heating heating, agitator, pressure relief
overboiling sensor	Yes	Yes	Yes	Yes with auto-supervision
torque limitation of drives	No	No	optional	Yes, pneumatic-mech. + electronically
variable speed control	lauter tun, brew kettle, optimal	Yes	Yes	lauter tun, lautering pump, brew kettle from 16 hl, MWP
network connection	No	No	No	Yes via Tempmatic 4/12
remote maintenance	No	No	Yes (optionally)	Yes
software updating	No	No	Yes	Yes, free of charges